

*SPECIFICATION AMENDMENTS*

Replace the paragraph beginning at page 3, line 14 with:

Figure 2 is a flowchart illustrating the steps taken to determine which transport to use in accordance with the teachings of the invention; and

Replace the paragraph beginning at page 3, line 16 with:

Figure 3 is a block diagram illustrating an embodiment of an operating system for directing data through a plurality of transport providers;

At page 3, line 18, insert:

Figure 4 is a block diagram illustrating OBEX services and OBEX transports in the operating system of figure 3;

Figure 5 is a block diagram illustrating the steps of sending an object between devices;

Figure 6a is a block diagram illustrating the steps of providing a service to a device through a transport provider; and

Figure 6b is a block diagram illustrating the functions of the interfaces of figure 6a.

At page 16, line 8, insert the following paragraph:

Turning now to figures 6a and 6b, the general steps in providing a service to a device through a transport is shown. The primary interface, such as the IOBEX interface is provided. As previously described, the primary interface has commands to enumerate transports and to enumerate devices. The transport interface, such as IOBEXTransport, IOBEXTransportSocket, and IOBEXTransportConnection is provided for communicating with the transports. A service interface, such as IOBEXService and IOBEXServiceConnection, is provided to determine when an incoming connection arrives and accepting the incoming connection. Once connected, a device interface, such as IOBEXDevice, is provided for communicating with the device.